



BODY 110 SEAL

Technical Data Sheet No 708

One component, waterborne sealant, 100% Acrylic

Suitable for sealing and bonding of metal sheets, wood and many other automotive and boat materials

Also suitable for exterior surfaces which are exposed to UV rays

It does not shrink, retains its shape

Remains permanently elastic and dries quickly

It can be rubbed on and can be painted over when it is "tack free", with all paint systems

General Technical Description

This is a one component, waterborne sealant. It is used for sealing and bonding of metal sheets, wood and many other automotive and boat materials, even for those directly exposed to UV light. It is ready to use. It remains elastic and does not shrink, retains its shape. It can be painted over with all paint systems, after drying. It can be applied with the cartridge. After use, clean all used tools with plenty of water.

Surface

Internal or external parts of the car body.

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL/BODY 771 ANTISIL FAST.

Make sure the surface is first wiped then air dried.



Make sure you always use appropriate face protection and good ventilation

Product Application: »» It is ideal for high quality bonding and sealing in the internal and external parts of the car body. It is also adequate for wood, boats and for exterior surfaces which are exposed to sunlight. Applicable with the cartridge. It can be painted over with all paint systems, after drying.



0%



Apply with the brush or spatula



200 - 1000µm (8 - 40 mil)



Drying time
3-12h / 23°C (73°F)



P320 - P1000



Synthetic paints
Acrylic paints



0%



4mm
5 - 6 bar (79 - 87 psi)
2 x 200 µm (8 mil)



3-8h / 23°C (73°F)



P320 - P1000



Synthetic paints
Acrylic paints



Always close tin after use



Store in a cool place



Always wear protective equipment



Follow the application instructions mentioned in this TDS

Flash Point:

-

Specific Gravity:

1.36 g/cm³

Solid Content (No thinner):

70% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 390 g/L.
2004/42/IB(e)(840)390

Theoretical Coverage:

-

Cleaning of equipment:

Clean after final use with plenty of water

Remarks:

- Allow for additional time for combi spray booths to reach the desired temperature
- It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

- Store in a cool place (+5°C - +25°C) (+41°F - +77°F) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 2 / 2017, December 2017